

SILICASTONE™

Incline

Designed for use on larger projects, this sophisticated product makes a significant aesthetic statement for any design project. Incline creates a seductive and subtle surface effect that truly comes to life when downlit, highlighting the dramatic and sophisticated surface effects of each Incline tile.

Colours




NATURAL
Textured



NATURAL
Honed




CHARCOAL
Textured



CHARCOAL
Honed



TEAL
Textured



TEAL
Honed

Sizes

250 X
50MM



250 X
100MM



THICKNESS OPTIONS

9-30mm

Specifications

CLASSIFICATION	BIII	THERMAL SHOCK	No evidence of damage
WATER ABSORPTION	8%	FROST RESISTANCE	No evidence of damage after 100 cycles
TILE LINEAR DIMENSIONS	+/- 2%	BOND STRENGTH	Resin - 6.4N/mm ² / Dispersion - 2.4N/mm ²
DIMENSION RECTANGULARITY	0.71%	REQUIRES SEALING	Yes
SURFACE THICKNESS	+/- 1.8%	INDOOR USE	Yes
STAIN RESISTANCE	Class 4	OUTDOOR USE	Yes
REACTION TO FIRE (CWT)	A1	THERMAL EXPANSION	Rate of Heating: 5 °C/minute
			<small>13 Thermal Expansion Coefficient 20-100°C in: is equal to for Direction X: 9.25E-6 °C⁻¹ 13 Thermal Expansion Coefficient 20-100°C in: is equal to for Direction Y: 9.38E-6 °C⁻¹</small>

For more information about this product or our full product range please contact us:
info@alusid.co.uk +44 (0)1772 429275 alusid.co.uk

ALUSID®