


SILICASTONE™

Crackle

Available in two slim format sizes, with every tile being unique in both colour and texture. Crackle glaze tiles are created by the top glaze being put through a process called crazing, giving each tile its distinctive look and feel. Crackle is perfect for use in any interior. Crackle tiles should be sealed once fixed.

Colours



CARTMEL CREAM

Gloss Varied Crackle Glaze

Sizes

200 X
100MM



300 X
100MM



THICKNESS OPTIONS

12mm

Specifications

CLASSIFICATION	BIII	THERMAL SHOCK	No evidence of damage
WATER ABSORPTION	12%	FROST RESISTANCE	No evidence of damage after 100 cycles
TILE LINEAR DIMENSIONS	+/- 2%	BOND STRENGTH	Resin - 6.4N/mm ² / Dispersion - 2.4N/mm ²
DIMENSION RECTANGULARITY	0.71%	REQUIRES SEALING	Yes
SURFACE THICKNESS	+/- 1.8%	INDOOR USE	Yes
STAIN RESISTANCE	Class 5	OUTDOOR USE	No
REACTION TO FIRE (CWT)	A1	THERMAL EXPANSION	Rate of Heating: 5 °C/minute

¹³ Thermal Expansion Coefficient 20-100°C in: is equal to for Direction X: 9.25E-6 °C⁻¹
¹³ Thermal Expansion Coefficient 20-100°C in: is equal to for Direction Y: 9.38E-6 °C⁻¹

For more information about this product or our full product range please contact us:
info@alusid.co.uk +44 (0)1772 429275 alusid.co.uk

ALUSID®