

# SILICASTONE™


## Weave

A product that will add a design statement to any interior. This exciting modular tile is designed for both indoor and outdoor application. It's a unique, deep relief tile that gives the designer several options for fixing both horizontally and vertically.


### Colours




**NATURAL**  
Textured



**NATURAL**  
Honed



**CHARCOAL**  
Textured



**CHARCOAL**  
Honed



**TEAL**  
Textured



**TEAL**  
Honed

### Sizes

250 X  
50MM



250 X  
100MM



#### THICKNESS OPTIONS

9-30mm

### Specifications

<b>CLASSIFICATION</b>	BIII	<b>THERMAL SHOCK</b>	No evidence of damage
<b>WATER ABSORPTION</b>	8%	<b>FROST RESISTANCE</b>	No evidence of damage after 100 cycles
<b>TILE LINEAR DIMENSIONS</b>	+/- 2%	<b>BOND STRENGTH</b>	Resin - 6.4N/mm <sup>2</sup> / Dispersion - 2.4N/mm <sup>2</sup>
<b>DIMENSION RECTANGULARITY</b>	0.71%	<b>REQUIRES SEALING</b>	Yes
<b>SURFACE THICKNESS</b>	+/- 1.8%	<b>INDOOR USE</b>	Yes
<b>STAIN RESISTANCE</b>	Class 4	<b>OUTDOOR USE</b>	Yes
<b>REACTION TO FIRE (CWT)</b>	A1	<b>THERMAL EXPANSION</b>	Rate of Heating: 5 °C/minute <small>13 Thermal Expansion Coefficient 20-100°C in: is equal to for Direction X: 9.25E-6 °C<sup>-1</sup> 13 Thermal Expansion Coefficient 20-100°C in: is equal to for Direction Y: 9.38E-6 °C<sup>-1</sup></small>

For more information about this product or our full product range please contact us:  
info@alusid.co.uk +44 (0)1772 429275 alusid.co.uk

**ALUSID®**