

<p style="text-align: center;">Manufacturer</p> <p style="text-align: center;"><b>ALUSID®</b></p>		Product Name:	<b>Terrazzo Reef</b>
Controlled and Reportable Materials Disclosure	Revision Date: <b>21/01/2022</b>	Issue: <b>B</b>	Description: <b>Ceramic Glass Surface</b>

Issue	Originator	Details of Change	Date
A	ABremner	Document is an Manufacturer declaration of the known ingredients within Alusid products as provided by suppliers and provide a guide to safe use	09/02/2021
B	ABremner	Updated to provide CAS numbers	19/01/2022

## Scope

This specification sets out Alusid Ltd (“Alusid”) materials disclosure requirements for materials used in the manufacture and delivery of products to our customers.

## Terms

Body – Body refers to the tile or surface main material, excluding any surface glaze or surface application.

Homogeneous Material - A material, as defined by the European Union Technical Adaptation Committee, that cannot be mechanically disjointed into different materials; homogenous materials are materials “of uniform composition throughout.” E.g Ceramics, glass

Glaze – Surface treatment applied to the surface of a tile or surface body

Reportable Substances - These substances are not currently banned but must be reported for other purposes.

Substance - A “Substance” is a chemical element, compound, has a CAS number, some materials may be made out of multiple compounds or substances

Substance Concentration – Concentration shall be expressed in percentages or where appropriate, parts per million (ppm) The formula for parts per million (ppm) is  $1,000,000 * \text{mass substance} / \text{mass of the homogeneous material}$ . Concentrations are unit- less, for example  $100 \text{ ppm} = 0.01\% = 100 \text{ mg/kg}$ .

## Product Identification and Classification

Common Name: Silicastone Ceramic Glass Surface

Synonyms: Solid Surface

Chemical Name : None

Chemical Family: Natural inorganic products

Chemical Formula: Not applicable to tiles or surfaces

CAS Reg. No.: Not applicable to tiles

Manufacturer: Alusid Ltd, Unit 6 Astra Business Centre, Roman Way Preston, PR25AP

Manufacturer <b>ALUSID®</b>		Product Name:	<b>Terrazzo Reef</b>
Controlled and Reportable Materials Disclosure	Revision Date: <b>21/01/2022</b>	Issue: <b>B</b>	Description: <b>Ceramic Glass Surface</b>

The finished, fired surfaces are odourless, stable, non-flammable, and **pose no immediate hazard to health**. If dust is produced by cutting tiles during installation or if dust is produced by any other operations (including demolition/removal projects) respiratory, hand and eye protection may be needed to prevent excess exposure to airborne particulates; only in this particular case an hazard to health could arise due to breathable crystalline silica.

Emergency Overview (dust/breathable crystalline silica):

Danger! Lung injury and Cancer Hazard GHS Classification (Global Harmonized Standard Classification):

- Carcinogenicity Category 2 (H350)
- Specific target organ toxicity, single exposure; Respiratory tract irritation - Category 3 (H335)
- Specific target organ toxicity, repeated exposure - Category 1A (H372) GHS Label, Hazards and Precautionary Statements GHS Pictogram:



Crystalline Silica: Category 3 (Respiratory tract irritation) (H335) Category 1A(Carcinogenicity)(H372)

Label Signal Word: Danger

Hazard Statements:

(H350) May cause CANCER (inhalation)

(H335) May cause respiratory irritation

(H372) Causes damage to organs (lung/respiratory) through prolonged or repeated exposure (inhalation)

### 3. Composition/information on ingredients

Tiles are mixtures of predominately Vitrified Ceramics, Soda Lime Glass and other naturally-occurring minerals including clays, that have been mixed with water and fired in a very high temperature kiln (> 1000°C – 1100) Tiles are manufactured in various shapes, sizes, and colours. These products do not contain asbestos.

Under normal condition these products do not release hazardous materials after installation and are not considered hazardous waste should disposal be necessary. Glazes contain lead bi-silicate frit.

Body Composition

Chemical name	CAS Number	Estimated % by total Wt.
Cordierite Pitcher waste, Vitrified	1302-88-1	45-55
Recycled Soda Lime Silicate Glass	2446523-50-6	25-35

Manufacturer <b>ALUSID®</b>		Product Name:	<b>Terrazzo Reef</b>
Controlled and Reportable Materials Disclosure	Revision Date: <b>21/01/2022</b>	Issue: <b>B</b>	Description: <b>Ceramic Glass Surface</b>

Crystalline silica as quartz, Vitreous china	14808-60-7	5-10
Kaolin	1332-58-7	3-5
Diiron trioxide, Hematite	1317-60-8	<0.5

#### 4. First aid measures

##### *Description of first aid measures*

Following skin contact: Wash with plenty of soap and water.

Following eye contact: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice if irritation persists.

Following inhalation: Take the patient outdoors and keep them warm and still.

##### *Most important symptoms and effects, both acute and delayed*

During the floor installation process, cutting stage may produce breathable crystalline silica. Prolonged and/or large-scale inhalation of breathable crystalline silica dust may cause pulmonary fibrosis, commonly known as silicosis. The main symptoms of silicosis are coughing and shortness of breath. Occupational exposure to breathable crystalline silica dust must be monitored and controlled.

##### *Indication of any immediate medical attention and special treatment needed*

Treatment: None

#### 5. Firefighting measures

Flash point (Method Used): N/A

Flammable limits:

LEL-Not Applicable

UEL- Not Applicable

Autoignition Temperature: N/A

Fire Extinguishing Media: N/A

Special Fire Fighting Procedures: N/A

Fire and Exposition hazards: N/A None Required

#### 6 Accidental release measures

Avoid creating excessive dust. Clean up dust with a vacuum system with a High-efficiency particulate (HEPA) air filter vacuum or damp sweeping. See Section 8 of this SDS concerning PPE information for clean-up.

#### 7. Handling and storage

<p style="text-align: center;">Manufacturer</p> <p style="text-align: center;"><b>ALUSID®</b></p>		<p>Product Name:</p>	<p><b>Terrazzo Reef</b></p>
<p>Controlled and Reportable Materials Disclosure</p>	<p>Revision Date: <b>21/01/2022</b></p>	<p>Issue: <b>B</b></p>	<p>Description: <b>Ceramic Glass Surface</b></p>

When cutting, grinding or removing, use equipment with integral dust collection and/or use local exhaust ventilation. **Use wet cutting methods to reduce generation of dust.** Use respiratory protection in the absence of effective engineering controls.

Do not store near acids. If tiles contact some acids, damage/discoloration to the surface may occur especially to the surface of highly glazed surfaces. Shelf life is unlimited provided the storage boxes are kept in a good condition.

## 8. Exposure controls/personal protection

### **Control parameters (ACGH)**

Total dust (TLV/TWA)

TLV TWA - 10 mg/m<sup>3</sup>  
TLV STEL - n.d.

Breathable Dust fraction (TLV-TWA)

TLV TWA - 3 mg/m<sup>3</sup>  
TLV STEL - n.d.

Crystalline Sylica as QUARTZ – Breathable fraction:

TLV TWA - 0.025 mg/m<sup>3</sup>  
TLV STEL - n.d.

### **Exposure controls**

Ventilation: Use adequate ventilation to keep exposure to dust below recommended exposure levels. Avoid inhalation of dust. The highest probability of silica exposure occurs during installation using dry cutting methods or during removal of installed tile or surface.

### **Wet cutting methods are recommended.**

Eye protection: Not required for normal use. In the absence of effective engineering controls, se dust-proof goggles or safety glasses with side shields. Contact lenses may absorb irritants. Do not wear contact lenses in work areas.

Hand/Skin protection: When cutting this product, cotton or leather work gloves should be worn to minimize skin exposure to dust and/or cuts. Wash hands prior to eating, drinking, or smoking, and at the end of the work shift, after cutting operations are conducted.

Respiratory protection: In the event of exposure levels higher than those stated in point 8.1, wearing a respiratory protection device compliant with national legal requirements is mandatory. Use of proper PPE it is still always recommended during tiles cutting, grinding and removing stages.

## 9. Physical and chemical properties

Appearance and colour: brittle solid, colour may vary, glazes also vary

Odour: Odourless

Melting point/freezing point: 1200C

Initial boiling point and boiling range: N/A

<p style="text-align: center;">Manufacturer</p> <p style="text-align: center;"><b>ALUSID®</b></p>		Product Name:	<b>Terrazzo Reef</b>
Controlled and Reportable Materials Disclosure	Revision Date: <b>21/01/2022</b>	Issue: <b>B</b>	Description: <b>Ceramic Glass Surface</b>

Flammability (solid/gas): Not inflammable  
Upper/lower flammability or explosive limit: N/A  
Vapour density: N/A  
Flash point: Evaporation rate: not flammable N/A  
Vapour pressure: N/A  
Solubility in water: N/A  
Specific Gravity (H<sub>2</sub>O = 1): >2  
Solubility in oil: N/A  
Partition coefficient: n-octanol/water: N/A  
Auto-ignition temperature: Not inflammable  
Decomposition temperature: N/A  
Viscosity: N/A  
Explosive properties: N/A  
Oxidising properties: N/A  
Volatility: 0 g/L Volatile Organic Comp.(VOCs)

#### 10. Stability and reactivity

Reactivity : Inert  
Chemical stability: stable in normal conditions  
Conditions to avoid: Contact with acid and strong alkali  
Stability: stable in normal conditions and use  
Incompatible materials: Acid and alkali  
Hazardous decomp. products: None  
Hazardous Polymerization: None

#### 11. Toxicological information

Tile products are mixtures of predominately Clays, Sands, Glass and other naturally-occurring mineral, that have been mixed with water and fired in a high temperature kiln. Tiles are odourless, stable, non-flammable, and pose no immediate hazard to health. **Surfaces are not designed to be used as food preparation surfaces.**

Respiratory, hand and eye protection may be needed to prevent excess exposure to airborne particulates if dust is produced by cutting tiles or if dust is produced by any other operations, including removal.

##### **Primary Routes of Exposure**

**None for intact surface.**

Inhalation and potential eye exposure to eyes, hands, or other body parts if contact is made with broken, and/or during procedures involving the cutting of tiles, and/or for operations involving the removal of installed tiles.

##### **Acute Effects**

**No acute effects from exposure to intact tile are known.**

Working with broken or cut tile produces a potential for cuts to the hands and exposed body parts. Acute effects such as eye irritation may occur if associated with high dust operations such as dry cutting tile or during the removal of tile surfaces.

<p style="text-align: center;">Manufacturer</p> <p style="text-align: center;"><b>ALUSID®</b></p>		<p>Product Name:</p>	<p><b>Terrazzo Reef</b></p>
<p>Controlled and Reportable Materials Disclosure</p>	<p>Revision Date:</p> <p><b>21/01/2022</b></p>	<p>Issue: <b>B</b></p>	<p>Description:</p> <p><b>Ceramic Glass Surface</b></p>

In very rare cases, symptoms of acute silicosis, a form of silicosis (a nodular pulmonary fibrosis) associated with exposure to respirable crystalline silica, may develop following acute exposure to extremely dusty environments generated from tile dust.

Signs such as laboured breathing and early fatigue may indicate silicosis; however, these symptoms can arise from many other causes. Care should be taken to reduce dust when working with any Alusid tile products

#### ***Chronic Effects***

***No chronic effects are known for exposure to intact tile.***

Long-term, continual exposure to respirable crystalline silica at or above allowable occupational exposure limits may lead to the development of silicosis (a nodular pulmonary fibrosis), and are associated with pulmonary tuberculosis, bronchitis, emphysema, and other airway diseases.

This type of exposure may also be related to the development of autoimmune disorders, chronic renal disease, and other adverse health effects.

Recent epidemiologic studies demonstrate that workers exposed to elevated silica concentrations have a significant risk of developing chronic silicosis. Signs such as laboured breathing and early fatigue may indicate silicosis; however, these symptoms can arise from many other causes.

#### ***Potential Adverse Interactions***

Silicosis may be complicated by severe mycobacterial or fungal infections and result in tuberculosis (TB). Epidemiologic studies have established that silicosis is a risk factor for developing TB. Any existing respiratory or pulmonary diseases may be complicated by exposure to respirable crystalline silica. Smoking may increase the risk of adverse effects if done in conjunction with occupational exposure to crystalline silica.

#### ***Carcinogen Status***

Breathable crystalline silica is classified by the International Agency for Research on Cancer (IARC) as a Group I Carcinogen (carcinogenic to humans). The National Toxicology Program (9th Report) lists respirable crystalline silica as Known to be a Human Carcinogen. USDOL/OSHA and NIOSH have recommended that crystalline silica be considered a potential occupational carcinogen.

#### ***Overview of Animal Testing Data***

Short term experimental studies of rats have found that intratracheal instillation of quartz particles leads to the formation of discrete silicotic nodules in rats, mice and hamsters.

#### ***Oral (silica) Lethality***

LD50 Rat oral >22,500 mg/kg LD50

Mouse oral >15,000 mg/kg LC50

Carp >10,000 mg/l (per 72 hr)

## **12. Ecological information**

Toxicity: Adopt good working practices and do not discharge the product into the environment.

<p style="text-align: center;">Manufacturer</p> <p style="text-align: center;"><b>ALUSID®</b></p>		<p>Product Name:</p>	<p><b>Terrazzo Reef</b></p>
<p>Controlled and Reportable Materials Disclosure</p>	<p>Revision Date: <b>21/01/2022</b></p>	<p>Issue: <b>B</b></p>	<p>Description: <b>Ceramic Glass Surface</b></p>

Persistence and degradability : N.A.

Bioaccumulative potential : N.A.

Mobility in soil : N.A.

Other adverse effects : None

### 13. Disposal considerations

Ceramic tiles are building materials. Waste treatment methods: Recover if possible or dispose in a certified landfill authorized to accept such material in accordance with the relevant local and national legislation.

### 14. Transport information

D.O.T Shipping Name: N/A

SIC code: 69072200

Hazard Class: Not Hazardous /Not regulated material)

ID Number: N/A

Marking: N/A

Label: N/A

Placard: N/A

Hazardous Substance/RQ: N/A

Shipping Description: Recycled Ceramic surfaces

Packaging References: None

### 15. Regulatory information

This product and/or its components have been previously introduced into U.S. commerce and is listed in the Toxic Substances Control Act (TSCA) Inventory of Chemicals in Commerce. Hence, it is subject to all applicable provisions and restrictions under TSCA 40 CFR Section 721 and 723.250.

This tile contains <1 percent by weight each of the following elements, which are SARA 313 Recordable: Antimony, Arsenic, Barium, Beryllium, Cadmium, Cobalt, Chromium, Copper, Manganese, Mercury, Nickel, Lead, Silver, Thallium, Tin, Titanium, Vanadium, and Zinc.

Title 22 Division 2, California Code of Regulation Chapter 3 (Proposition 65): This product contains a chemical or chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm.

This product or its components meets the following hazard definition(s) as defined by the Occupational Safety and Health Hazard Communication Standard (29 CFR Section 1910.1200):

Based on information presently available, this product does not meet any of the hazard definitions of 29 CFR Section 1910.1200.

**Please Note: The information in this data sheet provides information related to the potential hazards associated**

<p style="text-align: center;">Manufacturer</p> <p style="text-align: center;"><b>ALUSID<sup>®</sup></b></p>		<p>Product Name:</p>	<p><b>Terrazzo Reef</b></p>
<p>Controlled and Reportable Materials Disclosure</p>	<p>Revision Date: 21/01/2022</p>	<p>Issue: <b>B</b></p>	<p>Description: <b>Ceramic Glass Surface</b></p>

*with dusts which may be produced during cutting or otherwise changing the shape of the tile during installation and/or removal. Exposure to acid will release additional hazards*

**16. Other information**

NONE